# **WEATHERWELD**

## WW471145 Asphalt Emulsion



WW471145 - Weatherweld Asphalt Emulsion is the primary waterproofing component of WeatherWeld roofing systems and is applied simultaneously with WeatherWeld fiberglass. A colloid mixture of water, asphalt, and bentonite clay, WeatherWeld asphalt emulsion is water-carried, low odor, UV stable and 0 VOC.

PERFORMANCE		CERTIFICATIONS
PROPERTY	VALUE	
Appearance:	Thixotropic liquid	
Color:	Black	
Flash Point:	Non-Flammable.	
Maximum VOC:	0 g/l Calculated	APPROVED
Solids Content by Volume:	49-53% per ASTM D 2697	]
Viscosity (Brookfield):	8,000-15,000 cPs per ASTM D 2196	
		]
		MORE INFO

#### Packaging:

1 Gallon Cans 5 Gallon Pails 55 Gallon Drums 275 Gallon Totes Bulk Delivery

WeatherWeld - A Division of Liquiform Technologies Inc.

9757 7th St. #803 Rancho Cucamonga, CA 91730 | (888) 440-3224 | info@weatherweld.com | (888) 440-3224

# **EATHER WELD** WW471145 Asphalt Emulsion

#### Coverage:

30 to 45 gallons per 100 square feet depending on application.

#### Surface Preparation:

Surface must be clean, dry and in good condition. Remove all debris, loose gravel, and dirt from the roof by brooming or vacuuming and power-wash the entire roof.

#### Application:

Emulsion is spray applied using the WeatherWeld 3D Roof Printer. Emulsion is simultaneously applied with

glass fibers to provide a seamless reinforced roof membrane.

#### Cleanup:

Clean wet coating from hands and tools with soap and water. If dry, clean tools with kerosene, paint thinner

or mineral spirits.

#### Warnings:

Use appropriate gloves and other protective clothing when handling this product. EMPLOYERS should

obtain a copy of the Material Safety Data Sheet (MSDS) from your supplier or directly from WeatherWeld at

the toll free number or website below.

#### Warranty:

We, the manufacturer, warrant only that this product is free of defects, since many factors which affect the results obtained from this product - such as weather, workmanship, equipment utilized and prior condition of the substrate - are all beyond our control. We will replace at no charge any product proved to be defective within 12 months of purchase, provided it has been applied in accordance with our written directions for uses we recommended as suitable for this product. Proof of purchase must be provided.

DISCLAIMER OF WARRANTIES AND LIMITATION OF LIABILITY: THIS LIMITED WARRANTY IS IN LIEU OF ANY OTHER WARRANTIES EXPRESS OR IMPLIED INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FOR A PARTICULAR PURPOSE. MANUFACTURER SHALL HAVE NO LIABILITY OF ANY KIND BEYOND PRODUCT REPLACEMENT, INCLUDING FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES RESULTING FROM ANY DEFECTS OR ANY DELAYS CAUSED BY REPLACEMENT OR OTHERWISE. THIS LIMITED WARRANTY PROVIDES THE PURCHASER'S EXCLUSIVE REMEDY FOR ANY DEFECT IN THE PRODUCT.

### WeatherWeld - A Division of Liquiform Technologies Inc.

9757 7th St. #803 Rancho Cucamonga, CA 91730 | (888) 440-3224 | info@weatherweld.com | (888) 440-3224

Revised: 11/31/2023 WWTDS-001.pdf